



**VENTRY SOLUTIONS, INC.**

14128 N Hauser Lake Rd  
Hauser, ID 83854-5619  
(888) 257-8967 | (208) 773-1194 | (208) 777-0360 Fax  
info@ventry.com | VENTRY.COM

**BID SPECIFICATIONS**  
**LENTRY® PORTABLE LIGHT SYSTEM**  
**Model 2OPUPH**

1. LENTRY PORTABLE LIGHT Model 2OPUPH incorporates:
  - One all-terrain three-legged LENTRY Frame (US patent D684,309),
  - One Honda® EU-series 2200-watt generator,
  - One telescoping pole, and
  - One high output light.
2. LENTRY UNIT shall stand, with legs and pole fully extended, over 12.5 feet tall.
3. LENTRY UNIT shall have three independently adjustable, outward curving, powder-coated legs made of solid aluminum, which:
  - Allow the unit to rise twelve inches above the ground in order for the generator to be raised above sand, snow, water, and ground debris;
  - Allow the unit to be level when placed on stairs or uneven ground;
  - Protect the generator and keep it up off the ground, even when retracted.
4. LENTRY UNIT, without the light or pole attached, shall:
  - Measure 27 inches long x 15 inches wide x 21 inches high, and
  - Weigh less than 59 lbs., not including fuel and oil.
5. LENTRY UNIT shall include a LENTRY Optup Halogen light head which shall:
  - Produce 19,600 lumens of lights while using only 750 watts of power;
  - Be detachable from the pole using a Quick Release knob;
  - Weigh less than 7 lbs. and measure 9 inches long x 6.5 inches wide x 13 inches high; and
  - Be able to tip forward and back and rotate more than 360 degrees without repositioning the generator.
6. LENTRY UNIT's telescoping pole, identified as Hi-Lite height, shall:
  - Be detachable from the generator portion of the system by turning a knob on the frame;
  - Retract no less than 73 inches and extend no more than 138.5 inches (not including the light head); and
  - Have twist-lock mechanisms allowing the poles to be locked at any length in between their retracted and extended lengths.
7. LENTRY UNIT's power supply shall be a gasoline powered generator with inverter technology for fuel efficiency, super-quiet operation, and computer-safe power. The generator shall:
  - Have a rated wattage of 1800W (15A) and maximum wattage of 2200W (18.3A);
  - Power a 750 watt light for 6.8 hours on a 0.95-gallon tank of gas;
  - Feature 20A 125V duplex receptacles, NEMA plug 5-20P; and
  - Not exceed 57 dB at rated load and 48 dB at ¼ load.
8. LENTRY UNIT shall be covered by warranties of:
  - 3 years on the generator;
  - 2 years on the light head; and
  - 5 years on other components, workmanship, and materials.
9. LENTRY UNIT shall be available with these optional accessories:
  - Digital combination tachometer and hour meter, which tracks RPM and total hours.
  - Receiver Hitch Pole Mount that fits standard 2-inch receivers and holds any LENTRY telescoping pole and light
  - Truck-Mount hardware to hold a telescoping pole and light firmly to a wall, cabinet door, or side of truck

