



VENTRY SOLUTIONS, INC.

14128 N Hauser Lake Rd
Hauser, ID 83854-5619
(888) 257-8967 | (208) 773-1194 | (208) 777-0360 Fax
info@ventry.com | VENTRY.COM

BID SPECIFICATIONS
LENTRY® PORTABLE LIGHT SYSTEM
Model 2WIDES

1. LENTRY® PORTABLE LIGHT Model 2WIDES incorporates one all-terrain three-legged LENTRY Frame (US patent D684,309), one Honda® EU-series generator, one telescoping pole, and one high output light.
2. LENTRY UNIT shall stand, with legs and pole fully extended, over 3.5 feet tall.
3. LENTRY UNIT shall have three independently adjustable, outward curving, powder-coated legs made of solid aluminum, which:
 - Allow the unit to rise twelve inches above the ground in order for the generator to be level and raised above sand, snow, and water;
 - Allow the unit to be placed on stairs or uneven ground;
 - Allow the unit to straddle ground debris; and
 - Protect the generator and keep it up off the ground, even when retracted.
4. LENTRY UNIT shall include a LENTRY Panorama Halogen light head which shall:
 - Produce 35,000 lumens of lights while using 1500 watts of power;
 - Be detachable from the pole using a hex key or the optional Quick Release accessory;
 - Weigh less than 11 lbs. and measure 20 inches high x 17 inches wide x 7 inches deep; and
 - Be able to tip forward and back, without repositioning the generator, to aim at the ground or sky and rotate more than 360 degrees for side-to-side aiming.
5. LENTRY UNIT's telescoping pole, identified as Standard height, shall:
 - Be detachable from the generator portion of the system by turning a knob on the frame;
 - Retract (shorten) to 15.25 inches and extend (lengthen) to 25.75 inches (not including the light head); and
 - Have a twist-lock mechanism allowing the pole to be locked at any length in between the retracted and extended lengths.
6. LENTRY UNIT's power supply shall be a gasoline powered generator with inverter technology for fuel efficiency, super-quiet operation, and computer-safe power. The generator shall:
 - Have a rated wattage of 1800W (15A) and maximum wattage of 2200W (18.3A);
 - Power a 1500 watt light for 4.1 hours on a 0.95-gallon tank of gas;
 - Feature 20A 125V duplex receptacles, NEMA plug 5-20P; and
 - Not exceed 57 dB at rated load and 48 dB at ¼ load.
7. LENTRY UNIT, without the light or pole attached, shall be capable of fitting in a 21 inches high x 14.75 inches wide x 27.25 inches deep compartment and weigh less than 59 lbs., not including fuel and oil.



LENTRY PORTABLE LIGHT SYSTEM Model 2WIDES



VENTRY SOLUTIONS, INC.

14128 N Hauser Lake Rd

Hauser, ID 83854-5619

(888) 257-8967 | (208) 773-1194 | (208) 777-0360 Fax

info@ventry.com | VENTRY.COM

8. LENTRY UNIT shall be covered by warranties of:

- 3 years on the generator;
- 5 years on the light head; and
- 5 years on other components, workmanship, and materials.

9. LENTRY UNIT shall be available with these optional accessories:

- Digital Tiny Tach™ combination tachometer and hour meter, which tracks RPM and total hours.
- Quick Release, which allows easy connect/disconnect of light from pole without tools.