BID SPECIFICATIONS ALL-TERRAIN PORTABLE LIGHT SYSTEM

- 1. All-terrain portable light system incorporates
 - One all-terrain three-legged frame,
 - One 1000-watt generator,
 - Two telescoping poles,
 - Two high output LED lights, and
 - One case in which to store the two light heads.
- 2. System shall stand, with legs and poles fully extended, over 3.5 feet tall.
- 3. System shall have three independently adjustable, outward curving, powder-coated legs made of solid aluminum, which:
 - Allow the unit to rise eleven inches above the ground in order for the generator to be raised above sand, snow, water, and ground debris;
 - Allow the unit to be level when placed on stairs or uneven ground;
 - Protect the generator and keep it up off the ground, even when retracted.
- 4. System, without the lights or poles attached and not including the case, shall:
 - Measure 23.5 inches long x 14 inches wide x 19.5 inches high, and
 - Weigh less than 42 lbs., not including fuel and oil.
- 5. System shall include two LED light heads, each of which shall:
 - Produce 28,000 lumens of lights while using only 336 watts of power (56,000 lumens using 672 watts total);
 - Be detachable from the pole using a knob mounted at the bottom of each light head;
 - Weigh less than 10 lbs. and measure 14.5 inches long x 3.5 inches wide x 15 inches high; and
 - Be able to tip forward and back and rotate more than 360 degrees without repositioning the generator.
- 6. System shall include two telescoping poles, each of which shall:
 - Be detachable from the generator portion of the system by turning a knob on the frame;
 - Retract no less than 15 inches and extend no more than 26 inches each (not including the light heads); and
 - Have twist-lock mechanisms allowing the poles to be locked at any length in between their retracted and extended lengths.
- 7. System's power supply shall be a gasoline powered generator with inverter technology for fuel efficiency, super-quiet operation, and computer-safe power. The generator shall:
 - Have a rated wattage of 900W (7.5A) and maximum wattage of 1000W (8.3A);
 - Power two 336 watt lights for 4.5 hours on a 0.6-gallon tank of gas;
 - Feature 15A 125V duplex receptacles; and
 - Not exceed 50 dB(A) at rated load and 42 dB(A) at 1/4 load.
- 8. System shall include one injection molded plastic case which shall:
 - Be made in the USA of extreme-duty polypropylene copolymer resin;
 - Measure 33.5 inches long x 13 inches wide x 22 inches high;
 - Meet military standards for protection against air, water, theft and impacts (MIL-STD-810G);
 - Have polyethylene closed-cell inner foam, cut exactly to fit the two LED light heads, which will not disintegrate with sun or water and will protect and cushion the lights and provide extra energy/shock absorption; and
 - Feature two-step latches, multiple points for padlocks, and multiple recessed handles.
- 9. System shall be covered by warranties of:
 - 1 year on the generator;
 - 5 years on the light heads;
 - Lifetime on the case; and
 - 5 years on other components, workmanship, and materials.
- 10. System shall be available with these optional accessories:
 - Digital combination tachometer and hour meter, which tracks RPM and total hours.
 - Over-the-shoulder carrying strap made of strong nylon
 - Receiver Hitch Pole Mount that fits standard 2-inch receivers and holds any 1.75 inch diameter telescoping pole and light
 - Truck-Mount hardware to hold a telescoping pole and light firmly to a wall, cabinet door, or side of truck