BID SPECIFICATIONS ALL-TERRAIN PORTABLE LIGHT SYSTEM

- 1. All-terrain portable light system incorporates:
 - One all-terrain three-legged frame,
 - One 2200-watt generator,
 - One telescoping pole,
 - · One high output LED light, and
 - One case in which to store the light.
- 2. System shall stand, with legs and pole fully extended, over 8.5 feet tall.
- System shall have three independently adjustable, outward curving, powder-coated legs made of solid aluminum, which:
 - Allow the unit to rise twelve inches above the ground in order for the generator to be raised above sand, snow, water, and ground debris;
 - Allow the unit to be level when placed on stairs or uneven ground; and
 - Protect the generator and keep it up off the ground, even when retracted.
- 4. System, without the light or pole attached and not including the case, shall:
 - Measure 27 inches long x 15 inches wide x 21 inches high, and
 - Weigh less than 59 lbs., not including fuel and oil.
- 5. System shall include one LED light head which shall:
 - Produce 28,000 lumens of light and use only 336 watts of power;
 - Be detachable from the pole using a knob mounted at the base of the light head;
 - Weigh less than 10 lbs. and measure 14.5 inches long x 3.5 inches wide x 15 inches high; and
 - Be able to tip far forward and back and rotate more than 360 degrees without repositioning the generator.
- 6. System's telescoping pole shall:
 - Be detachable from the generator portion of the system by turning a knob on the frame;
 - Retract no less than 44 inches and extend no more than 84 inches (not including the light head); and
 - Have a twist-lock mechanism allowing the pole to be locked at any length in between the retracted and extended lengths.
- 7. System's power supply shall be a gasoline powered generator with inverter technology for fuel efficiency, super-quiet operation, and computer-safe. The generator shall:
 - Have a rated wattage of 1800W (15A) and maximum wattage of 2200W (18.3A);
 - Power a 336 watt light for 8.3 hours on a 0.95-gallon tank of gas;
 - Feature 20A 125V duplex receptacles, NEMA plug 5-20P; and
 - Not exceed 57 dB at rated load and 48 dB at ¼ load.
- 8. System shall include one injection molded plastic case, which shall:
 - Be made in the USA of extreme-duty polypropylene copolymer resin;
 - Measure 22.5 inches long x 8.5 inches wide x 18 inches high;
 - Meet military standards for protection against air, water, theft and impacts (MIL-STD-810G);
 - Have polyethylene closed-cell inner foam cut exactly to fit the LED light head, which will not disintegrate with sun or water and will protect and cushion the light and provide extra energy/shock absorption;
 - Be submersible, water-tight, and dust-proof; and
 - Feature two-step latches, multiple points for padlocks, and multiple recessed handles.
- 9. System shall be covered by warranties of:
 - 1 years on the generator;
 - 5 years on the light head;
 - · Lifetime on the case; and
 - 5 years on other components, workmanship, and materials.
- 10. System shall be available with these optional accessories:
 - Digital combination tachometer and hour meter, which tracks RPM and total hours.
 - Receiver Hitch Pole Mount that fits standard 2-inch receivers and holds any 1.75 inch diameter telescoping pole and light.
 - Truck-Mount hardware to hold a telescoping pole and light firmly to a wall, cabinet door, or side of truck.