

BID SPECIFICATIONS

ALL-TERRAIN PORTABLE LIGHT SYSTEM

1. All-terrain portable light system incorporates:
 - One all-terrain three-legged frame,
 - One 2200-watt generator,
 - One telescoping pole,
 - One 2-Headed LED light head, and
 - A case in which to store the light head and pole.
2. System shall stand, with legs and pole fully extended, over 8.5 feet tall.
3. System shall have three independently adjustable, outward curving, powder-coated legs made of solid aluminum, which:
 - Allow the unit to rise twelve inches above the ground in order for the generator to be raised above sand, snow, water, and ground debris;
 - Allow the unit to be level when placed on stairs or uneven ground; and
 - Protect the generator and keep it up off the ground, even when retracted.
4. System, without the light head or pole attached and not including the case, shall:
 - Measure 27 inches long x 15 inches wide x 21 inches high, and
 - Weigh less than 59 lbs. (without fuel and oil).
5. System shall include one 2-Headed LED light head which shall:
 - Consist of two high-output LED lights mounted to a single horizontal bar,
 - Produce 28,000 lumens from each of the two LED heads while using only 336 watts, together totaling 56,000 lumens and drawing 672 watts;
 - Be detachable from the pole using a knob mounted at the base of the light head;
 - Weigh less than 23 lbs. and measure 30 inches long x 6 inches wide x 18 inches high;
 - Allow each of the two LED heads to operate independently, tipping forward and back and rotating more than 360 degrees without repositioning the generator; and
 - Have separate on/off switches for each LED head but one cord to run both, leaving one of the generator's two receptacles free.
6. System's telescoping pole shall:
 - Be detachable from the generator portion of the system by turning a knob on the frame;
 - Retract no less than 44 inches and extend no more than 84 inches (not including the light head); and
 - Have a twist-lock mechanism allowing the pole to be locked at any length in between the retracted and extended lengths.
7. System's power supply shall be a gasoline powered generator with inverter technology for fuel efficiency, super-quiet operation, and computer-safe power. The generator shall:
 - Have a rated wattage of 1800W (15A) and maximum wattage of 2200W (18.3A);
 - Power two 336 watt lights for 7.1 hours on a 0.95-gallon tank of gas;
 - Feature 20A 125V duplex receptacles, NEMA plug 5-20P; and
 - Not exceed 57 dB at rated load and 48 dB at ¼ load.
8. System shall come with an injection molded plastic case, which shall:
 - Be made in the USA of extreme-duty polypropylene copolymer resin;
 - Measure 49.5 inches long x 9 inches wide x 21.5 inches high;
 - Meet military standards for protection against air, water, theft and impacts (MIL-STD-810G);
 - Have polyethylene closed-cell inner foam, cut exactly to fit the 2-Headed LED light head and pole, which will not disintegrate with sun or water and will protect and cushion the light and provide extra energy/shock absorption.
 - Be submersible, water-tight, and dust-proof; and
 - Feature two-step latches, multiple points for padlocks, and multiple recessed handles.
9. System shall be covered by warranties of:
 - 3 years on the generator;
 - 5 years on the light head;
 - Lifetime on the case; and
 - 5 years on other components, workmanship, and materials.

10. System shall be available with these optional accessories:

- Digital combination tachometer and hour meter, which tracks RPM and total hours.
- Receiver Hitch Pole Mount that fits standard 2-inch receivers and holds any 1.75 inch diameter telescoping pole and light.
- Truck-Mount hardware to hold a telescoping pole and light firmly to a wall, cabinet door, or side of truck.