

# LENTRY® UTILITY LIGHT SYSTEM

**NEW PRODUCT**

The **LENTRY UTILITY SYSTEM** by Ventry Solutions, Inc. is bright, portable, and all-terrain that lights large areas regardless of the scene, site, or season. They deploy and break down in seconds, include either one or two high output, extra tall "XT" LEDs, and lets you **SEE AND BE SEEN**.

For those who already have a power source available or who currently have a LENTRY SYSTEM and would like to run a second light in another location, the **LENTRY UTILITY SYSTEM** is a sound investment for greater safety on any job site or emergency scene.

## V-Spec LED (both single & 2-Headed)

- Uses a combination of flood and spot lighting
- Instant-on / instant-off (no cool down time)
- Low operating temperatures
- Rated for 50,000 hours
- Maintenance free; solid state electronics
- Lights have a *tool-free* Quick Release for quick setup and break down
- Each light head tips far forward/back and rotates 450°

## Military-grade case

- Meets strict US Military standards for protection against air, water, and impact
- Will not warp, rust, rot, bend, crack, or shatter
- Foam interior will not disintegrate with sun or water

## Sign Stand

- Telescoping legs with four positive locking positions: vertical, normal, and two for uneven terrain
- Stainless tell guide plate provides a smooth clamping motion as adapter is tightened to stand
- Kick release legs for easy leg adjustments

The 2-Headed LENTRY UTILITY LIGHT is available with Case C3422 (model TWHDX-SS-C34) or Case C5022 (model TWSPX-SS-C50) and comes with or without the sign stand.

Each LENTRY UTILITY LIGHT is available with one of three cases: C2318, C3422, or C5022.



**Your work has enough risks.  
Make sure you can see.**

## Specifications

### V-SPEC LED LIGHT

|              |                           |
|--------------|---------------------------|
| Light Output | 28,000 lumens             |
| Light Input  | 120V 336W (2.8A)          |
| Size (LxWxH) | 14.5 x 3.5 x 14.75 inches |
| Weight       | 10 lbs                    |

### 2-HEADED V-SPEC LIGHT

|              |                                   |
|--------------|-----------------------------------|
| Light Output | 56,000 lumens total (28,000 each) |
| Light Input  | 120V 672W (5.6A) total            |
| Size (LxWxH) | 29.5 x 6 x 18 inches              |
| Weight       | 22 lbs                            |

### XT HEIGHT POLE

|        |                      |
|--------|----------------------|
| Length | 44 inches, retracted |
| Weight | 4.5 lbs              |

### SIGN STAND

|              |                               |
|--------------|-------------------------------|
| Size (LxWxH) | 30 x 7 x 8 inches (collapsed) |
| Weight       | 16 lbs                        |

### CASE C2318

|              |                                       |
|--------------|---------------------------------------|
| Model        | Included with models ending in "-C23" |
| Holds        | V-Spec Light Head                     |
| Size (LxWxH) | 22.5 x 8.5 x 18 inches                |
| Weight       | 11.5 lbs                              |

### CASE C3422

|              |  |
|--------------|--|
| Model        | Included with models ending in "-C34"    |
| Holds        | Two V-Spec or 2-Headed V-Spec Light Head |
| Size (LxWxH) | 33.5 x 13 x 22 inches                    |
| Weight       | 29.5 lbs                                 |

### CASE C5022

|              |   |
|--------------|---|
| Model        | Included with models ending in "-C50"                     |
| Holds        | One or two V-Spec or 2-Headed V-Spec & up to two XT poles |
| Size (LxWxH) | 49.5 x 9 x 21.5 inches                                    |
| Weight       | 30.5 lbs  |

**Fully extended, the LENTRY UTILITY LIGHT stands 9.5- to 11.25-feet tall.**

This single LED system is available with Case C2318 (model SPECX-SS-C23) or Case C5022 (model SPECX-SS-C50).



**LENTRY® All-Terrain,  
Portable Lights**

**Ventry Solutions, Inc.**

(888) 257-8967 | (208) 773-1194

14128 N Hauser Lake Rd, Hauser, ID 83854 USA

info@ventry.com

**VENTRY.COM**

© 2019 Ventry Solutions, Inc. 190823